

Bright SOLID SHINE Laser LCD Projectors Blend High Performance and Low Running Costs for Best Value in Mid-sized Venues



PT-MZ770 Series		
	PT-MZ770/L	PT-MW730/L
Brightness	7,500 lm	
Resolution	WUXGA	WXGA
Contrast	3,000,000:1*1	

Note: PT-MZ770L and PT-MW730L offer the same performance as PT-MZ770 and PT-MW730 respectively, but come without a lens.

Outstanding Brightness and Picture Quality

- SOLID SHINE Laser technology with 3LCD optical engine serves bright, vivid, and detailed pictures
- Up to 7,500 lm brightness delivered from compact and lightweight body
- 3,000,000:1*1 dynamic contrast via digitally modulated laser light source improves text legibility and assists with crisp and accurate pictures
- Available in WUXGA*2 for detailed Full HD video reproduction and high-resolution images, text, and graphics
- Detail Clarity Processor 4 enhances image clarity and sharpness
- Daylight View Basic optimizes pictures for best visibility in bright environments
- DICOM Simulation Mode*3 for medical presentations
- Color Adjustment Function corrects color variations in multi-projector applications

High Efficiency and Low Maintenance

- Laser light source returns 20,000 hours*4 of continuous operation (no exchange required)
- Inorganic LCD panels and inorganic polarizing plates maintain high image quality for extended periods
- Extended 20,000-hour*5 maintenance-free period for reusable Eco Filter*6
- One-way airflow design improves efficacy of lens-assembly sealing to maintain high brightness and picture quality
- Dust-resistant cabinet design improves filter-module and air-intake-duct sealing
- ECO Management System effectively reduces power consumption

Easy Setup and Operation

- DIGITAL LINK/HDMI® support transmission of uncompressed 4K signal (PT-MZ770/L only)
- Powered lens shift, zoom, and focus via remote control
- Supports wireless projection with optional module (ET-WM300)
- Corner Keystone & Curved Screen Correction
- Network function via LAN for stress-free remote operation
- Supports free Multi Monitoring & Control Software
- Incorporates LinkRay™ Light ID Transmission function delivering information to smartphones*7, ideal for signage and exhibition/display applications

*1 With Dynamic Contrast 1/2, Image Mode set to Dynamic. *2 PT-MZ770/L has WUXGA and PT-MW730/L WXGA resolution. *3 This product is not a medical instrument. Do not use for actual medical diagnosis. *4 Around this time, original light source brightness will have decreased by approximately 50 %. With IEC62087: 2008 Broadcast content, Dynamic Contrast [2], in environments with 0.15 mg/m³ of particulate matter. Estimated maintenance time varies depending on environment. *5 In environments with 0.15 mg/m³ of particulate matter. Estimated maintenance time varies depending on environment. *6 Eco Filter is designed to be washed and reused twice. If filter is not sufficiently clean after washing with water, replacement is advised. *7 Requires purchase and activation of a LinkRay™ service contract.

Specifications (Tentative)

Model	PT-MZ770/MZ770L	PT-MW730/MW730L
LCD panel	Panel size	19.3 mm (0.76") diagonal (16:10 aspect ratio)
	Display method	Transparent LCD panel (x 3, R/G/B)
	Drive method	Active matrix
	Pixels	2,304,000 (1920 x 1200) x 3, total of 6,912,000 pixels
Lens	PT-MZ770/MW730: Powered zoom (throw ratio 1.6–2.8:1), F = 1.7–2.3, f = 26.8–45.5 mm PT-MZ770L/MW730L: Optional powered zoom/focus lenses	
Light source	Laser diode (Class 1) (Class 3R for US models)	
Screen size (diagonal)	1.02–10.16 m (40–400 in), 16:10 aspect ratio 1.52–10.16 m (60–400 in) with the ET-ELW22, 16:10 aspect ratio	
Brightness*1	7,500 lm	
Center-to-corner uniformity*1	90 %	
Contrast	3,000,000:1 (Dynamic Mode/Dynamic Contrast 1/2)	
Resolution	1920 x 1200 pixels	1280 x 800 pixels
Optical axis shift	Vertical (from center of screen)	±67 % (powered) (for supplied lens [ELS20]/ELW20/ELT20/ELT21, ELW22; max. ±60 %, ELW21; cannot use optical axis shift function)
	Horizontal (from center of screen)	±35 % (powered) (for supplied lens [ELS20]/ELW20/ELT20/ELT21, ELW22; max. ±30 %, ELW21; cannot use optical axis shift function)
Keystone correction range*2	Vertical: ±25°, Horizontal: ±30°	Vertical: ±35°, Horizontal: ±35° (Up to a total of ±55° during simultaneous horizontal and vertical correction)
Installation	Horizontal/Vertical, free 360-degree installation	
Terminals	HDMI IN	HDMI 19-pin x 2 (Deep Color, compatible with HDCP), audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz/32 kHz)
	RGB 1 IN	BNC x 5 (RGB or YPbPr/YCbCr x 1)
	RGB 2 IN	D-sub HD 15-pin (female) x 1 (compatible with component input)
	VIDEO IN	Pin jack x 1 (composite video)
	MONITOR OUT	D-sub HD 15-pin (female) x 1 (RGB x 1) (compatible with RGB or YPbPr/YCbCr)
	AUDIO IN	Pin jack x 2 (L–R), M3 stereo mini jack x 2
	AUDIO OUT	M3 stereo mini-jack x 1 for output
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
	REMOTE 1 IN	D-sub 9-pin (female) x 1 for external control (parallel)
	REMOTE 2 IN	M3 x 1 for wired remote control
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX, compatible with PjLink™ (Class 2)
	DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection, 100Base-TX, compatible with PjLink™ (Class 2), HDCP, Deep Color
	Memory Viewer/Pairing	USB (Type A) x 1
	DC OUT	USB (Type A) x 1, DC 5 V/2 A*3
Power supply	100–240 V AC, 50/60 Hz	
Power consumption	TBD	TBD
Built-in speaker	10 W (monaural)	
Operating noise*1	35 dB (NORMAL/ECO Mode), TBD (Quiet Mode)	
Filter	x 1, estimated maintenance time: approx. 20,000 hours*4	
Cabinet materials	Molded plastic (PC + ABS)	
Dimensions (W x H x D)	PT-MZ770/MW730: 560 x 205*5 x 443 mm (22 1/16" x 8 1/16"*5 x 17 7/16") (with supplied lens) PT-MZ770L/MW730L: 560 x 205*5 x 428 mm (22 1/16" x 8 1/16"*5 x 16 7/32") (without lens)	
Weight*6	PT-MZ770/MW730: Approximately 17.1 kg (37 lbs) (with supplied lens) or less PT-MZ770L/MW730L: Approximately 16.3 kg (35.7 lbs) (without lens)	
Operating environment	Operating temperature: 0 °C–45 °C (32 °F–113 °F)*7, operating humidity: 20 %–80 % (no condensation)	
Applicable software/application	Wireless Manager for Windows/Mac, Logo Transfer Software, Multi Monitoring & Control Software, Smart Projector Control, Plug and Share, Wireless Projector Apps for iOS/Android™	

Note: PT-MZ770L and PT-MW730L deliver the same performance as PT-MZ770 and PT-MW730 but respectively come without a lens.

*1 Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. *2 With supplied lens. Value differs when correction for both directions is operated. *3 On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready. *4 Under conditions with 0.15 mg/m³ of particulate matter (based on tests by the American Society of Heating, Refrigerating, and Air-Conditioning Engineers [ASHRAE], and the Japanese Building Maintenance Association). Estimated maintenance time varies depending on environment. *5 With legs at shortest position. *6 Average value. May differ depending on models. *7 Brightness is limited at operating temperatures higher than 36 °C (96 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level.

Optional Accessories

■ **Zoom Lens**
ET-ELW20 / ET-ELW22
ET-ELT20 / ET-ELT21/
ET-ELS20*

* Available only in the US and Europe.

■ **Fixed Lens**
ET-ELW21

■ **Ceiling Mount Bracket**
ET-PKD120H (for high ceiling)
ET-PKD120S (for low ceiling)

■ **Bracket Assembly**
ET-PKE301B

■ **Replacement Filter Unit**
ET-RFM100

■ **Wireless Module**
ET-WM300

■ **Easy Wireless Stick**
ET-UW100*

* Availability varies depending on region.

■ **DIGITAL LINK Switcher**
ET-YFB200G

■ **Digital Interface Box**
ET-YFB100G

■ **Early Warning Software**
ET-SWA100 Series

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. PjLink™ is a registered trademark or pending trademark in Japan, the United States, and other countries and regions. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. All other trademarks are the property of their respective trademark owners. © 2018 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojector
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of February 2018.

PT-MZ770PRE1 Printed in Japan.